

QTY

PART No.

FB22397 09-18 Dodge Ram Front Bumper





REQUIRED TOOLS

Die Grinder 18mm Socket 5mm Socket

Help of a friend

KIT CONTAINS

Front Bumper	1
Nut Plate	4
M12 Nyloc Nut	8
M12 Washer	8
Plastic Washer	8
Winch Plate	1
Flange Bolt	2
Flange Nut	2
Trim Accents	2
Small Nut Plate	2
Small Nyloc Nut	4

550 W. PINE LAKE RD., SUITE 2, NORTH LIMA, OHIO 44452 330.423.6446 WWW.FISHBONEOFFROAD.COM



PART No.

FB22397 09-18 Dodge Ram Front Bumper

1) **REMOVE EXISTING BUMPER**

Begin removing your vehicle's existing bumper and grille. We show how to do this in another video over at <u>www.fishboneoffroad.tv</u>

Remove the sensors and sensor wiring harness.

2) SETUP

Depending on the state of your vehicle, with your die grinder, grind out the show hole so that the included nut plates can slide through.





In the back of the bumper, install 2 of the nut plates into the outboard bumper-to-frame brackets, and screw on the included plastic washers to help keep them in place.



If applicable, install your sensors and wiring harness at this time.

Install your winch onto the winch plate.



3) INSTALL THE BUMPER

With the help of a friend and the 4 of the included m12 nuts and washer, secure the bumper to the frame rails with an 18mm socket.



1



PART No.

FB22397 09-18 Dodge Ram Front Bumper



Install the winch plate with the remaining nut plates and hardware into the inboard bumper brackets.



With the 2 flanged bolts and hex nuts, secure the bottom of the winch plate.



Install the two trim accents with the small nutplates and small nyloc nuts with a 5mm socket.





2137400



PART No.

FB22397 09-18 Dodge Ram Front Bumper



Install your pod lights.



Reinstall your grille.



2137400

550 W. PINE LAKE RD., SUITE 2, NORTH LIMA, OHIO 44452 330.423.6446 WWW.FISHBONEOFFROAD.COM