



INSTALLATION INSTRUCTIONS

Product: Adjustable Track Bar Rebuild Kit

Part Number: JKS7202

Applications: JKSOGS121, OGS122, OGS123, OGS159

877-533-7557 • jks@sporttruckusainc.com • www.jksmfg.com
491 W. Garfield Avenue, Coldwater, MI 49036

Welcome

CONGRATULATIONS on purchasing a Track Bar Rebuild Kit from JKS Manufacturing. We are committed to providing you with the best products available and your satisfaction is our first priority.

PLEASE READ these Installation Instructions carefully, and save them for future reference, as they contain important installation and maintenance information.

Tools Required

- H Frame Press

Parts

| Description | QTY |
|-----------------|-----|
| Rubber Bushing | 2 |
| Track Bar Decal | 1 |

Installation

□ TRACK BAR REMOVAL

- Securely block wheels to prevent accidental movement of vehicle.
- Remove track bar from vehicle. Original installation instructions can be referenced if necessary.

□ RUBBER BUSHING

□ 1. REMOVAL

- Position press plates so that the rubber bushing eye is fully supported.
- Using a large socket or other appropriate tooling, press the old bushing out of the bushing eye. The socket used should be as large as possible while still fitting through the bushing eye.
- Clean any corrosion or debris from the inner surface.

□ 2. INSTALLATION

- Place the new bushing and control arm eye into the press. Ensure the two components are aligned.
- Using appropriate tooling, press the bushing into place until the lip of the bushing is flush with the bushing eye.

□ FINAL STEPS

- Reinstall track bar. Reference original installation instructions if necessary.
- Verify jam nut is tight and did not move.
- If needed, a replacement decal is included.

Maintenance

Check torque specifications regularly.

©2015 JKS Manufacturing
Revision Date 03/11/2021